


ALFRA ROTABEST® – V 32



V 32

Core drill dimensions	Ø 12.0 - 32.0 mm
Cutting depth	30.0 mm
Counterboring	Ø 10.0 - 32.0 mm
Arbors	19 mm Weldon shank
1-speed gearbox	450 rpm
Stroke	45 mm
Power consumption	900 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Tool force (10 mm)/ magnetic adhesion strength	2,100 N / 16,000 N
Magnetic base	95 x 200 mm
Weight	12.5 kg

Motor	
Compact, lying	
Gearboxes	
Compact mitre gear	
Slide	
2-sided column guide	
Operation	
Space-saving - through ratchet	
Magnet	
Metal rings	✓
Performance and weight optimisation	✓
Made in Germany	✓

Scope of delivery	
<ul style="list-style-type: none"> • Metal core drilling machine V 32 • Coolant pressure bottle • Carrying case • Allen key for Weldon arbor • Seat belt • Ejector pin 6.35 x 74 mm (specially for Rotabest® V32) • Operating instructions • incl. 1 core drill free 	



Prod.-No.

ALFRA Rotabest® V32	230 Volt	18710
ALFRA Rotabest® V32	110 Volt	18710.110