

## HSS spiraalboren DIN 1869 Type 125-1



02/2023

**Toepassing:** Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

**Verpakking:** per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212510100	1,00	100	60	15,00	v
0212510150	1,50	100	60	17,04	v
0212510200	2,00	125	85	15,80	x
0212510250	2,50	140	95	19,13	v
0212510300	3,00	150	100	20,12	v
0212510320	3,20	155	105	20,13	x
0212510330	3,30	155	105	20,13	x
0212510350	3,50	165	115	22,07	x
0212510400	4,00	175	120	22,21	v
0212510420	4,20	175	120	22,21	x
0212510450	4,50	185	125	24,94	v
0212510500	5,00	195	135	25,85	v
0212510550	5,50	205	140	34,82	v
0212510600	6,00	205	140	38,26	v
0212510650	6,50	215	150	46,54	v
0212510680	6,80	225	155	51,36	x
0212510700	7,00	225	155	51,36	x
0212510750	7,50	225	155	53,28	x
0212510800	8,00	240	165	66,50	v
0212510850	8,50	240	165	68,59	x
0212510900	9,00	250	175	68,87	x
0212510950	9,50	250	175	71,47	v
0212511000	10,00	265	185	72,94	v
0212511020	10,20	265	185	104,46	x
0212511050	10,50	265	185	104,46	x
0212511100	11,00	280	195	131,02	v
0212511150	11,50	280	195	139,71	x
0212511200	12,00	295	205	172,85	x
0212511250	12,50	295	205	199,26	x
0212511300	13,00	295	205	206,90	v