

## HSS spiraalboren DIN 1869 Type 125-2



02/2023

**Toepassing:** Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

**Verpakking:** per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	*
0212520150	1,50	150	100	23,20	x
0212520200	2,00	160	110	24,96	v
0212520300	3,00	190	130	21,24	x
0212520350	3,50	210	145	25,23	v
0212520400	4,00	220	150	28,09	v
0212520450	4,50	235	160	30,89	v
0212520500	5,00	245	170	32,94	v
0212520550	5,50	260	180	45,48	v
0212520600	6,00	260	180	52,00	v
0212520650	6,50	275	190	65,50	v
0212520680	6,80	290	200	70,90	x
0212520700	7,00	290	200	67,83	x
0212520750	7,50	290	200	77,84	v
0212520800	8,00	305	210	80,22	v
0212520850	8,50	305	210	45,32	x
0212520900	9,00	320	220	83,24	v
0212520950	9,50	320	220	85,48	v
0212521000	10,00	340	235	97,04	v
0212521050	10,50	340	235	147,13	x
0212521100	11,00	365	250	172,85	v
0212521150	11,50	365	250	199,26	x
0212521200	12,00	375	260	229,32	x
0212521250	12,50	375	260	246,69	x
0212521300	13,00	375	260	256,99	x