

HSS spiraalboren DIN 1869 Type 125-2



03/2022

Toepassing: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	*
0212520150	1,50	150	100	21,70	x
0212520200	2,00	160	110	23,35	v
0212520300	3,00	190	130	19,87	x
0212520350	3,50	210	145	23,60	v
0212520400	4,00	220	150	26,28	v
0212520450	4,50	235	160	28,90	v
0212520500	5,00	245	170	30,81	v
0212520550	5,50	260	180	42,55	v
0212520600	6,00	260	180	48,64	v
0212520650	6,50	275	190	61,28	v
0212520680	6,80	290	200	66,33	x
0212520700	7,00	290	200	63,45	x
0212520750	7,50	290	200	72,82	v
0212520800	8,00	305	210	75,04	v
0212520850	8,50	305	210	42,39	x
0212520900	9,00	320	220	77,87	v
0212520950	9,50	320	220	79,96	v
0212521000	10,00	340	235	90,78	v
0212521050	10,50	340	235	137,63	x
0212521100	11,00	365	250	161,69	v
0212521150	11,50	365	250	186,40	x
0212521200	12,00	375	260	214,52	x
0212521250	12,50	375	260	230,77	x
0212521300	13,00	375	260	240,40	x