

HSS spiraalboren DIN 1869 Type 125-3



02/2023

Toepassingen: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212530200	2,00	200	135	26,70	v
0212530250	2,50	225	150	33,97	v
0212530300	3,00	240	160	37,70	v
0212530350	3,50	265	180	30,89	v
0212530400	4,00	280	190	35,45	v
0212530420	4,20	280	190	36,93	x
0212530450	4,50	295	200	36,93	x
0212530500	5,00	315	210	48,28	x
0212530550	5,50	330	225	66,14	v
0212530600	6,00	330	225	68,87	v
0212530650	6,50	350	235	92,77	x
0212530700	7,00	370	250	98,57	v
0212530750	7,50	370	250	110,48	v
0212530800	8,00	390	265	111,82	v
0212530850	8,50	390	265	117,85	x
0212530900	9,00	410	280	117,85	v
0212530950	9,50	410	280	123,74	v
0212531000	10,00	430	295	132,13	x
0212531050	10,50	430	295	187,44	v
0212531100	11,00	455	310	210,06	v
0212531150	11,50	455	310	224,21	v
0212531200	12,00	480	330	111,85	x
0212531250	12,50	480	330	271,93	x
0212531300	13,00	480	330	271,93	v