

HSS spiraalboren DIN 1869 Type 125-3



03/2022

Toepassingen: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212530200	2,00	200	135	24,98	v
0212530250	2,50	225	150	31,78	v
0212530300	3,00	240	160	35,27	v
0212530350	3,50	265	180	28,90	v
0212530400	4,00	280	190	33,16	v
0212530420	4,20	280	190	34,55	x
0212530450	4,50	295	200	34,55	x
0212530500	5,00	315	210	45,17	x
0212530550	5,50	330	225	61,88	v
0212530600	6,00	330	225	64,42	v
0212530650	6,50	350	235	86,78	x
0212530700	7,00	370	250	92,21	v
0212530750	7,50	370	250	103,35	v
0212530800	8,00	390	265	104,60	v
0212530850	8,50	390	265	110,25	x
0212530900	9,00	410	280	110,25	v
0212530950	9,50	410	280	115,75	v
0212531000	10,00	430	295	123,60	x
0212531050	10,50	430	295	175,34	v
0212531100	11,00	455	310	196,50	v
0212531150	11,50	455	310	209,74	v
0212531200	12,00	480	330	103,84	x
0212531250	12,50	480	330	254,37	x
0212531300	13,00	480	330	254,37	v