

## HSS spiraalboren DIN 1869 Type 125-2



2020

**Toepassing:** Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

**Verpakking:** per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	*
0212520150	1,50	150	100	18,48	v
0212520200	2,00	160	110	19,88	v
0212520250	2,50	180	120	16,92	v
0212520300	3,00	190	130	16,92	v
0212520320	3,20	200	135	20,10	v
0212520350	3,50	210	145	20,10	v
0212520400	4,00	220	150	22,38	v
0212520420	4,20	220	150	24,61	v
0212520450	4,50	235	160	24,61	v
0212520500	5,00	245	170	26,24	v
0212520550	5,50	260	180	36,23	v
0212520600	6,00	260	180	41,42	v
0212520650	6,50	275	190	52,18	v
0212520680	6,80	290	200	56,48	x
0212520700	7,00	290	200	54,03	v
0212520750	7,50	290	200	62,01	v
0212520800	8,00	305	210	63,90	v
0212520850	8,50	305	210	63,10	v
0212520900	9,00	320	220	66,31	v
0212520950	9,50	320	220	68,09	v
0212521000	10,00	340	235	77,30	v
0212521020	10,20	340	235	117,20	v
0212521050	10,50	340	235	117,20	v
0212521100	11,00	365	250	137,69	v
0212521150	11,50	365	250	158,73	v
0212521200	12,00	375	260	182,67	v
0212521250	12,50	375	260	196,51	v
0212521300	13,00	375	260	204,71	v