

## HSS spiraalboren DIN 1869 Type 125-3



2020

**Toepassingen:** Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

**Verpakking:** per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212530200	2,00	200	135	21,27	v
0212530250	2,50	225	150	27,06	v
0212530300	3,00	240	160	30,03	v
0212530320	3,20	250	170	24,61	x
0212530350	3,50	265	180	24,61	v
0212530400	4,00	280	190	28,24	v
0212530420	4,20	280	190	29,42	x
0212530450	4,50	295	200	29,42	v
0212530500	5,00	315	210	38,46	v
0212530550	5,50	330	225	52,69	v
0212530600	6,00	330	225	54,86	v
0212530650	6,50	350	235	73,90	v
0212530680	6,80	370	250	78,52	x
0212530700	7,00	370	250	78,52	v
0212530750	7,50	370	250	88,01	v
0212530800	8,00	390	265	89,07	v
0212530850	8,50	390	265	93,88	v
0212530900	9,00	410	280	93,88	v
0212530950	9,50	410	280	98,57	v
0212531000	10,00	430	295	105,25	v
0212531020	10,20	430	295	149,31	x
0212531050	10,50	430	295	149,31	v
0212531100	11,00	455	310	167,33	v
0212531150	11,50	455	310	178,60	v
0212531200	12,00	480	330	97,70	v
0212531250	12,50	480	330	216,61	v
0212531300	13,00	480	330	216,61	v