

HSS spiraalboren DIN 1869 Type 125-1

2021



Toepassing: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212510100	1,00	100	60	12,40	v
0212510150	1,50	100	60	14,09	v
0212510200	2,00	125	85		v
0212510250	2,50	140	95	15,82	x
0212510300	3,00	150	100	16,64	v
0212510320	3,20	155	105	16,64	v
0212510330	3,30	155	105	16,64	v
0212510350	3,50	165	115	18,25	v
0212510400	4,00	175	120	18,36	v
0212510420	4,20	175	120	18,36	v
0212510450	4,50	185	125	20,63	v
0212510500	5,00	195	135	21,37	v
0212510550	5,50	205	140	28,79	v
0212510600	6,00	205	140	31,64	v
0212510650	6,50	215	150	38,48	v
0212510680	6,80	225	155	42,46	v
0212510700	7,00	225	155	42,46	v
0212510750	7,50	225	155		v
0212510800	8,00	240	165	54,98	v
0212510850	8,50	240	165	56,72	v
0212510900	9,00	250	175	56,94	v
0212510950	9,50	250	175	59,09	v
0212511000	10,00	265	185	60,31	v
0212511020	10,20	265	185	86,37	x
0212511050	10,50	265	185	86,37	v
0212511100	11,00	280	195	108,34	x
0212511150	11,50	280	195	115,52	x
0212511200	12,00	295	205	142,92	x
0212511250	12,50	295	205	164,76	x
0212511300	13,00	295	205	171,07	x