

HSS spiraalboren DIN 1869 Type 125-2



2021

Toepassing: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	*
0212520150	1,50	150	100	19,18	v
0212520200	2,00	160	110	20,64	v
0212520300	3,00	190	130	17,56	v
0212520350	3,50	210	145	20,86	v
0212520400	4,00	220	150	23,23	v
0212520450	4,50	235	160	25,55	v
0212520500	5,00	245	170	27,24	v
0212520550	5,50	260	180	37,61	v
0212520600	6,00	260	180	42,99	v
0212520650	6,50	275	190	54,16	v
0212520680	6,80	290	200	58,63	x
0212520700	7,00	290	200	56,08	v
0212520750	7,50	290	200	64,37	v
0212520800	8,00	305	210	66,33	v
0212520850	8,50	305	210	37,47	v
0212520900	9,00	320	220	68,83	v
0212520950	9,50	320	220	70,68	v
0212521000	10,00	340	235	80,24	v
0212521050	10,50	340	235	121,65	v
0212521100	11,00	365	250	142,92	v
0212521150	11,50	365	250	164,76	v
0212521200	12,00	375	260	189,61	v
0212521250	12,50	375	260	203,98	v
0212521300	13,00	375	260	212,49	v