

HSS spiraalboren DIN 1869 Type 125-2



10/2021

Toepassing: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	*
0212520150	1,50	150	100	20,83	x
0212520200	2,00	160	110	22,40	v
0212520300	3,00	190	130	19,07	x
0212520350	3,50	210	145	22,65	v
0212520400	4,00	220	150	25,22	v
0212520450	4,50	235	160	27,74	v
0212520500	5,00	245	170	29,57	v
0212520550	5,50	260	180	40,83	v
0212520600	6,00	260	180	46,68	v
0212520650	6,50	275	190	58,81	v
0212520680	6,80	290	200	63,65	x
0212520700	7,00	290	200	60,89	x
0212520750	7,50	290	200	69,89	v
0212520800	8,00	305	210	72,02	v
0212520850	8,50	305	210	40,68	x
0212520900	9,00	320	220	74,73	v
0212520950	9,50	320	220	76,74	v
0212521000	10,00	340	235	87,12	v
0212521050	10,50	340	235	132,09	x
0212521100	11,00	365	250	155,18	v
0212521150	11,50	365	250	178,89	x
0212521200	12,00	375	260	205,87	x
0212521250	12,50	375	260	221,47	x
0212521300	13,00	375	260	230,71	x