

## HSS spiraalboren DIN 1869 Type 125-3



10/2021

**Toepassingen:** Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

**Verpakking:** per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212530200	2,00	200	135	23,97	v
0212530250	2,50	225	150	30,50	v
0212530300	3,00	240	160	33,84	v
0212530350	3,50	265	180	27,74	v
0212530400	4,00	280	190	31,83	v
0212530420	4,20	280	190	33,16	x
0212530450	4,50	295	200	33,16	x
0212530500	5,00	315	210	43,34	x
0212530550	5,50	330	225	59,38	v
0212530600	6,00	330	225	61,83	v
0212530650	6,50	350	235	83,29	x
0212530700	7,00	370	250	88,49	v
0212530750	7,50	370	250	99,19	v
0212530800	8,00	390	265	110,38	v
0212530850	8,50	390	265	105,80	x
0212530900	9,00	410	280	105,80	v
0212530950	9,50	410	280	111,09	v
0212531000	10,00	430	295	118,62	x
0212531050	10,50	430	295	168,27	v
0212531100	11,00	455	310	188,58	v
0212531150	11,50	455	310	201,28	v
0212531200	12,00	480	330	106,08	x
0212531250	12,50	480	330	244,12	x
0212531300	13,00	480	330	244,12	v